



TECHNICAL DATA SHEET

PRODUCT TEKNILID 1205

MATERIAL DESCRIPTION: Paper/Polyester/Peelable Adhesive/Aluminum Foil/Vinyl Composite Heat Seal

STRUCTURE: 25# Paper/0.00048" PET/Peelable Adhesive/0.001" Aluminum Foil/1.75# Vinyl

TYPICAL APPLICATIONS: Food, Pharmaceutical and Cosmetic packaging structures requiring high oxygen and moisture barrier properties which also provides a Child Resistant (CR) peel/push feature. Sealable to PVC and PVdC.

PHYSICAL AND CHEMICAL PROPERTIES

<u>Property</u>	<u>Typical Value</u>	<u>Units</u>	<u>Test Method</u>
Gauge:	0.0040	inch	ASTM D 374
Basis Weight	87.5	lbs/R	ASTM D 646
Yield:	4930	sq.in./lb.	ASTM D 646

Property data represented above are typical and are not specifications.

The information supplied on this Tech-Data Sheet is believed to be accurate but is based on laboratory tests which do not simulate actual use conditions. NO REPRESENTATION, GUARANTEE OR WARRANTIES OF ANY KIND ARE MADE AND TEKNI-PLEX INC. SPECIFICALLY DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Tekni-Plex inc. shall not be liable for and the customer assumes all risk and liability for any use or handling of any material beyond Tekni-Plex's direct control. Regardless of recommendations made, all uses of lining material should be tested and verified for suitability in the specific intended application.