



TECHNICAL DATA SHEET

PRODUCT TEKNILID 1207

MATERIAL DESCRIPTION: Laminated paper/Aluminum Foil/Polyolefin Film Composite

STRUCTURE: 26# Paper/Adhesive/0.001" Aluminum Foil/0.002" Film

TYPICAL APPLICATIONS: Food, Pharmaceutical and Cosmetic lidding stock for applications requiring a peelable seal to polypropylene or polyethylene and high oxygen and moisture barrier properties.

PHYSICAL AND CHEMICAL PROPERTIES

<u>Property</u>	<u>Typical Value</u>	<u>Units</u>	<u>Test Method</u>
Gauge:	0.0058	inch	ASTM D 374
Basis Weight	108.9	lbs/R	ASTM D 646
Yield:	3965	sq.in./lb.	ASTM D 646

Property data represented above are typical and are not specifications.

The information supplied on this Tech-Data Sheet is believed to be accurate but is based on laboratory tests which do not simulate actual use conditions. NO REPRESENTATION, GUARANTEE OR WARRANTIES OF ANY KIND ARE MADE AND TEKNI-PLEX INC. SPECIFICALLY DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Tekni-Plex inc. shall not be liable for and the customer assumes all risk and liability for any use or handling of any material beyond Tekni-Plex's direct control. Regardless of recommendations made, all uses of lining material should be tested and verified for suitability in the specific intended application.