



TECHNICAL DATA SHEET

PRODUCT TEKNILID 1208

MATERIAL DESCRIPTION: Laminated Paper/Polyester/Aluminum Foil/Vinyl Composite Heat Seal

STRUCTURE: 26# Paper/Adhesive/0.00048" PET/Adhesive/0.001" Aluminum Foil/1.75# Vinyl

TYPICAL APPLICATIONS: Food, Pharmaceutical and Cosmetic lidding stock for applications requiring high oxygen and moisture barrier properties, which also provides a Child Resistant (CR) feature.

PHYSICAL AND CHEMICAL PROPERTIES

| <u>Property</u> | <u>Typical Value</u> | <u>Units</u> | <u>Test Method</u> |
|-----------------|----------------------|--------------|--------------------|
| Gauge: | 0.0036 | inch | ASTM D 374 |
| Basis Weight | 84.2 | lbs/R | ASTM D 646 |
| Yield: | 5131 | sq.in./lb. | ASTM D 646 |

Property data represented above are typical and are not specifications.

The information supplied on this Tech-Data Sheet is believed to be accurate but is based on laboratory tests which do not simulate actual use conditions. NO REPRESENTATION, GUARANTEE OR WARRANTIES OF ANY KIND ARE MADE AND TEKNI-PLEX INC. SPECIFICALLY DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Tekni-Plex inc. shall not be liable for and the customer assumes all risk and liability for any use or handling of any material beyond Tekni-Plex's direct control. Regardless of recommendations made, all uses of lining material should be tested and verified for suitability in the specific intended application.