



TECHNICAL DATA SHEET
PRODUCT - TEKNILID HS 165

MATERIAL DESCRIPTION: Aluminum Foil coated with Heatsealable Polyester

STRUCTURE: 0.001” Aluminum Foil/0.00048” Polyester

TYPICAL APPLICATIONS: Lidding Material for Food, Pharmaceutical and Cosmetic blister packs requiring high oxygen and moisture barrier properties. Peelable to PET, and PVC.

PHYSICAL AND CHEMICAL PROPERTIES

| <u>Property</u> | <u>Typical Value</u> | <u>Units</u> | <u>Test Method</u> |
|-----------------|----------------------|--------------|--------------------|
| Gauge: | 0.0015 | inch | ASTM D 374 |
| Basis Weight | 56.1 | lbs/R | ASTM D 646 |
| Yield: | 7700 | sq.in./lb. | ASTM D 646 |

Property data represented above are typical and are not specifications.

The information supplied on this Tech-Data Sheet is believed to be accurate but is based on laboratory tests which do not simulate actual use conditions. NO REPRESENTATION, GUARANTEE OR WARRANTIES OF ANY KIND ARE MADE AND TEKNI-PLEX INC. SPECIFICALLY DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Tekni-Plex inc. shall not be liable for and the customer assumes all risk and liability for any use or handling of any material beyond Tekni-Plex's direct control. Regardless of recommendations made, all uses of lining material should be tested and verified for suitability in the specific intended application.