



TECHNICAL DATA SHEET

PRODUCT TEKNILID WSPPE

MATERIAL DESCRIPTION: Polyester/White Polyethylene/Aluminum Foil/Polyester/Peelable Film

STRUCTURE: 0.00048" PET/0.00075" WH PE/0.001" Aluminum Foil/0.00048" PET/0.002" Peelable Film

TYPICAL APPLICATIONS: A lidding foil which is peelable to PP or PE intended for Food, Pharmaceutical and Cosmetic packaging structures requiring high oxygen and moisture barrier properties. This material has excellent puncture and chemical resistance. A bright white exterior makes an excellent printing surface.

PHYSICAL AND CHEMICAL PROPERTIES

<u>Property</u>	<u>Typical Value</u>	<u>Units</u>	<u>Test Method</u>
Gauge:	0.0047	inch	ASTM D 374
Basis Weight	105.0	lbs/R	ASTM D 646
Yield:	4110	sq.in./lb.	ASTM D 646

Property data represented above are typical and are not specifications.

The information supplied on this Tech-Data Sheet is believed to be accurate but is based on laboratory tests which do not simulate actual use conditions. NO REPRESENTATION, GUARANTEE OR WARRANTIES OF ANY KIND ARE MADE AND TEKNI-PLEX INC. SPECIFICALLY DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Tekni-Plex inc. shall not be liable for and the customer assumes all risk and liability for any use or handling of any material beyond Tekni-Plex's direct control. Regardless of recommendations made, all uses of lining material should be tested and verified for suitability in the specific intended application.